



MICROCOPY REJOLUTION TEST CHART
NATIONAL BUREAU OF STANDARDS-1963-A

AD-A166 460



OPTICAL PROPERTIES OF BLOW-OFF PARTICULATES

Earl J. Davis
Ravindran Periasamy
University of Washington
Department of Chemical Engineering
Seattle, WA 98195

29 February 1984

SELECTE APR 1 0 1986

Technical Report

CONTRACT No. DNA 001-82-C-0224

Approved for public release; distribution is unlimited.

THIS WORK WAS SPONSORED BY THE DEFENSE NUCLEAR AGENCY UNDER RDT&E RMSS CODE B344082466 X99QAXSG00046 H2590D.

Prepared for
Director
DEFENSE NUCLEAR AGENCY
Washington, DC 20305-1000

DTIC FILE COPY

86 1 08 063

UNCLASSIFIED		
SECURITY CLASSIFICATION OF	5،⊷"	PAGE

AR A166460

		REPORT DOCU	MENTATION	PAGE		
18 REPORT SECURITY CLASSIFICATION UNCLASSIFIED	N		TO. RESTRICTIVE	VIARKINGS		
2a SECURITY CLASSIFICATION AUTHO	ORITY		3 DISTRIBUTION	N/AVAILABILITY C	OF REPORT	
			Approved	for public	release; d	istribution
26. DECLASSIFICATION, DOWNGRADI N/A since UNCLASSIFIE		LE	is unlimi	ited.		
4 PERFORMING ORGANIZATION REP	ORT NUMBE	R(S)	5. MONITORING	ORGANIZATION	REPORT NUMBER	₹(S)
IPC Project 3485; UW Pr	oject 65	5-4319	DNA-TR-84	l-69		
64. NAME OF PERFORMING ORGANIZ	ZATION	6b. OFFICE SYMBOL		ONITORING ORGA	ANIZATION	
University of Washingto	n	(If applicable)	Director Defense N	luclear Agen	су	
6c ADDRESS (City, State, and 21P Coo Department of Chemical Mail Stop BF-10 Seattle, Washington 981	Engineer	ring	1	ity, State, and ZIF on , DC 20305	•	
9a. NAME OF FUNDING SPONSORING ORGANIZATION	5	8b OFFICE SYMBOL (If applicable)	9 PROCUREMEN DNA 001-8	IT INSTRUMENT I	DENTIFICATION '	NUMBER
Bc. ADDRESS (City, State, and ZIP Cod	•)		10. SOURCE OF	FUNDING NUMBE	35	
			PROGRAM	PROJECT	TASK	WORK UNIT
Į		,	ELEMENT NO	NO	NO _	ACCESSION NO
11 TITLE (Include Security Classificat			62715H	X99QAXS	G	DH006209
Technical 16 SUPPLEMENTARY NOTATION This work was sponsored X99QAXSG00046 H2590D.		0801 +0 840131 Defense Nucle	14 DATE OF REPO 1984, Feb Agency unde	ruary 29	11	
17 COSATI CODES		18 SUBJECT TERMS	Continue on reven	se if necessary an	id identify by bi	ock number)
	-GROUP	Aerosols >	. 7	Albedo 🤊	2B10w-04	f F articulates
20 6		Complex Refrac	tive Index,			cattering
4 2 19 ABSTRACT (Continue on reverse		Optical Proper		Thermal Bus	tal -	
The results of the properties of dust part Using techniques and eq indices, particle sizes function of the wavelen from solar furnace expe contract.	second icles ge uipment , and al gth of triments	phase of baseli enerated in simu developed by the bedos of therma the laser light performed by Se	ne studies o lated nuclea e Frincipal l dust parti source. The ience Applic	r explosion Investigato culates wer particulat	s are preson, complex measured ses were ob-	ented. refractive as a tained
20. DISTRIBUTION / AVAILABILITY OF UNCLASSIFIED/UNLIMITED 22a NAME OF RESPONSIBLE INDIVID	SAME AS	RPT. DTIC USERS	UNCLASS			SVA2801
Betty L. Fox			(202) 325-	(Include Area Cod 7042	DNA/ST	II

DD FORM 1473, 84 MAR

33 APR edition may be used until exhausted.
All other editions are obsolete.

SECURITY CLASSIFICATION OF THIS PAGE

UNCLASSIFIED

UNCLASSIFIED SECURITY CLASSIFICATION OF THIS PAGE		
Į.		
		:
<u>.</u>		
	,	
		\$
1		

SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED

SUMMARY

This document is a report of the measurements of the light-scattering properties of blow-off particulates generated in simulated thermonuclear blasts. The thermal dust particles studied were generated in experiments performed by Science Applications Inc. under a separate DNA contract, using a solar furnace in Odeillo, France. The samples obtained from Science Applications Inc. consisted of filters, wall-wipings and loose dust taken from various locations in the solar furnace, and they correspond to several soil samples placed in the furnace for the tests.

The data reported include particle size, complex refractive index and albedo measurements obtained for three wavelengths of light in the visible (blue-green) range of the spectrum of electromagnetic radiation; 457.9, 488.0 and 514.5 nm. Earlier, measurements were made at 632.8 nm. These light-scattering data were obtained by suspending single, charged particles in an electrodynamic balance in the path of a polarized laser beam. The equipment, techniques and methods of data analysis are outlined herein.

TOTAL CONTRACTOR CONTR

The light-scattering data are supplemented by scanning electron micrographs (SEM) and EDAX (energy dispersive x-ray spectrometry) analyses, which provide information on the sizes, shapes and chemical composition of the particles. The EDAX analyses indicate that most of the dust studied was mixed silicates of aluminum, calcium, iron and potassium. Particle dimensions ranged from about 0.5 μ m to 100 μ m. The complex refractive index (m = m₁ - im₂) was found to have a real component, m₁, in the range 1.481 - 1.723, which is consistent with available data on the bulk refractive index of silicates and clays. The imaginary component, m₂, was small (m₂ < 0.06) compared with results available for highly absorbing particulates such as carbon particles (m₂ = 0.6 - 1.0). The particle albedos were found to be in the range 0.49 - 0.99.

PREFACE

The work reported here represents Phase II of baseline studies on the light-scattering properties of blow-off particulates. Phase I involved the development and testing of equipment, techniques and computer software, and the results of Phase I were summarized in Report number DNA 6274F, dated April 1983. That initial work was supported under Contract Number DNA 001-80-C-0213.

Phase II was continued at the Institute of Paper Chemistry (IPC) in Appleton, Wisconsin, but in August 1983 the Principal Investigator, Dr. E. James Davis, joined the faculty of chemical engineering at the University of Washington. His light-scattering laboratory was re-established at the University, and the research on Phase II was continued there under a subcontract with IPC.

This research provides information on the scattering and absorption properties in the visible region of the spectrum of electromagnetic radiation needed to interpret and assess field measurements of dust particles generated in a simulated thermonuclear explosion.

CONVERSION TABLE

To convert from	to	multiply by
A, Angstrom Units	m, meters	1.0E-10
μ m , micrometers	m, meters	1.0E-06
nm, nanometers	m, meters	1.0E-09

Accesi	on For	
DTIC	ounced	
By Distrib	ution/	
A	vailability C	codes
Dist	Avail and Special	
A-1		
	(OUALITY INSIFEOTED

TABLE OF CONTENTS

Section		Page
	SUMMARY	. 1
	PREFACE	. 2
	CONVERSION TABLE	. 3
	LIST OF ILLUSTRATIONS	. 5
	LIST OF TABLES	. 10
1	OBJECTIVES	. 11
	1.1 BACKGROUND	. 11
	1.1.1 Light Scattering Theory	. 11
	1.1.2 Principles of the Electrodynamic Balance .	. 15
2	THE EXPERIMENTAL APPARATUS AND DATA ANALYSIS	. 18
	2.1 THE EXPERIMENTAL SYSTEM	. 18
	2.2 INTERPRETATION OF THE DATA	. 21
3	RESULTS	. 24
	3.1 SAMPLE IDENTIFICATION	. 24
	3.2 ELECTRON MICROSCOPY	. 24
	3.3 LIGHT SCATTERING PHASE FUNCTIONS	. 45
4	DISCUSSION OF RESULTS	. 56
APP	ENDIX	
	I EXPERIMENTAL PHASE FUNCTION DIAGRAMS FOR THE DUST PARTICLES	. 63

<u>Figure</u>		Page
1	The dependence of scattered intensity I , on optical size α and angle θ for a refractive index m = 1.696 - i0.0	13
2	The effects of scattering angle θ and m_2 on the scattering intensity for $m_1 = 1.55$ and $\alpha = 10.0$	14
3	The electrodynamic balance/light scattering photometer and peripheral equipment	16
4	An exploded view of the electrodynamic balance	16
5	The electric circuitry for the picobalance	18
6	Raw light scattering data from a dust particle, λ = 457.9 nm	20
7	An SEM of loose dust from Run 57	26
8	An SEM of wall wipings from Run 57	26
9	An SEM of loose dust from Run 69	28
10	An SEM of loose dust from Run 1180	28
11	An SEM of wall wipings from Run 136 at lower magnification (X200)	29
12	An SEM of wall wipings from Run 136 for a magnification (X1000)	29
13	An SEM of wall wipings from Run 136 at high magnification (X2400)	30
14a	An SEM for a bottom filter from Run 57	31
14b	An elemental analysis (EDAX) for a bottom filter from Run 57	31
15a	An SEM for a wall wiping from Run 57	32
15b	An elemental analysis for a wall wiping from Run 57	32
16a	An SEM for a wall wiping from Run 60	33
16b	An elemental analysis for a wall wiping from Run 60	33
17a	An SEM for a wall wiping from Run 69	34
17b	An elemental analysis for a wall wiping from Run 69	34
18 a	An SEM for a bottom filter from Run 69	35
18b	An elemental analysis for a bottom filter from Run 69.	35

<u>Figure</u>		<u>Page</u>
19a	An SEM for a wall wiping from Run 101	36
19b	An elemental analysis for a wall wiping from Run 101 .	36
20 a	An SEM for a wall wiping from Run 104	37
20b	An elemental analysis for a wall wiping from Run 104 .	37
21a	An SEM for a wall wiping from Run 107	38
21b	An elemental analysis for a wall wiping from Run 107 .	38
22 a	An SEM for a wall wiping from Run 108	39
22b	An elemental analysis for a wall wiping from Run 108 .	39
23a	An SEM for a wall wiping from Run 136	40
23b	An elemental analysis for a wall wiping from Run 136 .	40
24a	An SEM for a wall wiping from Run 138	41
2 4 b	An elemental analysis for a wall wiping from Run 138 .	41
25a	An SEM for a wall wiping from Run 147	42
25b	An elemental analysis for a wall wiping from Run 147 .	42
26a	An SEM for a wall wiping from Run 1180	43
26b	An elemental analysis for a wall wiping from Run 1180 .	43
27	Experimental phase function data for a particle from Run 60 for λ = 457.9 nm compared with Mie Theory for α = 5.01 and m = 1.705 - i 0.054	46
28	Experimental phase function data for a particle from Run 60 for λ = 488.0 nm compared with Mie theory for α = 4.91 and m = 1.590 - i0.049	47
29	Experimental phase function data for a particle from Run 60 for λ = 514.5 nm compared with Mie theory for α = 5.38 and m = 1.571 - i0.018	48
30	Experimental phase function data for a particle from Run 1180 for λ = 457.9 nm compared with Mie theory for α = 9.61 and m = 1.719 - i0.029	50
31	Experimental phase function data for a particle from Run 1180 for λ = 488.0 nm compared with Mie theory for	51

ged Tesesseral sessesser Interesses (Andresses andresses appropriate sessesses assesses from

Figure		Page
32	Experimental phase function data for a particle from Run 1180 for λ = 514.5 nm compared with Mie theory for α = 9.30 and m = 1.709 - i0.026	52
33	Computed phase functions based on mean values of α and m for particles from Runs 57 (*), 60 (#) and 60 (+)	53
34	Computed phase functions based on mean values of α and m for particles from Runs 69 (*), 104 (#) and 107 (+)	54
35	Computed phase functions based on mean values of α and m for particles from Runs 108 (*), 136 (#) and 138 (+)	55
36	Computed phase functions for a Sphere for $\alpha = 10$, $m_1 = 16$ and $m_2 = 0.0$ (*), 0.025 (#) and 0.05 (+)	57
A1	Experimental phase function data for a particle from Run 57 for λ = 457.9 nm compared with Mie theory for α = 12.6 and m = 1.551 - i0.003	64
A2	Experimental phase function data for a particle from Run 57 for λ = 488.0 nm compared with Mie theory for α = 12.8 and m = 1.525 - i0.004	65
A3	Experimental phase function data for a particle from Run 57 for λ = 514.5 nm compared with Mie theory for α = 12.9 and m = 1.508 - i0.005	66
A4	Experimental phase function data for a particle from Run 57 for λ = 457.9 nm	67
A5	Experimental phase function data for a particle from Run 57 for λ = 488.0 nm	68
A6	Experimental phase function data for a particle from Run 57 for λ = 514.5 nm	69
A7	Experimental phase function data for a particle from Run 60 for λ = 457.9 nm compared with Mie theory for α = 4.60 and m = 1.626 - i0.036	70
A8	Experimental phase function data for a particle from Run 60 for λ = 488.0 nm compared with Mie theory for α = 4.84 and m = 1.600 - i0.030	71
А9	Experimental phase function data for a particle from Run 60 for λ = 514.5 nm compared with Mie theory for α = 4.62 and m = 1.633 - i0.026	72
A10	Experimental phase function data for a particle from Run 69 for λ = 457.9 nm compared with Mie theory for α = 12.5 and m = 1.562 - i0.003	73

Figure		<u>Page</u>
A11	Experimental phase function data for a particle from Run 69 for λ = 488.0 nm compared with Mie theory for α = 11.8 and m = 1.557 - i0.005	74
A12	Experimental phase function data for a particle from Run 69 for λ = 514.5 nm compared with Mie theory for α = 11.4 and m = 1.490 - i0.012	75
A13	Experimental phase function data for a particle from Run 69 for λ = 457.9 nm	76
A14	Experimental phase function data for a particle from Run 69 for λ = 488.0 nm	77
A15	Experimental phase function data for a particle from Run 69 for λ = 514.5 nm	78
A16	Experimental phase function data for a particle from Run 104 for λ = 457.9 nm compared with Mie theory for α = 12.2 and m = 1.601 - i0.024	79
A17	Experimental phase function data for a particle from Run 104 for λ = 488.0 nm compared with Mie theory for α = 12.2 and m = 1.593 - i0.007	80
A18	Experimental phase function data for a particle from Run 104 for λ = 514.5 nm compared with Mie theory for α = 12.4 and m = 1.573 - i0.008	81
A19	Experimental phase function data for a particle from Run 107 for λ = 488.0 nm compared with Mie theory for α = 12.4 and m = 1.574 - i0.007	82
A20	Experimental phase function data for a particle from Run 107 for λ = 514.5 nm compared with Mie theory for α = 12.5 and m = 1.559 - i0.005	83
A21	Experimental phase function data for a particle from Run 108 for λ = 457.9 nm compared with Mie theory for α = 12.8 and m = 1.529 - i0.005	84
A22	Experimental phase function data for a particle from Run 108 for λ = 488.0 nm compared with Mie theory for α = 12.9 and m = 1.510 - i0.005	85
A23	Experimental phase function data for a particle from Run 108 for λ = 514.5 nm compared with Mie theory for α = 13.1 and m = 1.481 - i0.007	86
A24	Experimental phase function data for a particle from Run 136 for λ = 488.0 nm compared with Mie theory for α = 12.4 and m = 1.582 - i0.002	87

the second reported seconds and the second seconds are second assessed to

Figure	EIST OF TEEOSTRATIONS	Page
A25	Experimental phase function data for a particle from Run 136 for λ = 457.9 nm	88
A26	Experimental phase function data for a particle from Run 136 for λ = 488.0 nm	89
A27	Experimental phase function data for a particle from Run 136 for λ = 514.5 nm	90
A28	Experimental phase function data for a particle from Run 136 for λ = 457.9 nm	91
A29	Experimental phase function data for a particle from Run 136 for λ = 488.0 nm	92
A30	Experimental phase function data for a particle from Run 136 for λ = 514.5 nm	93
A31	Experimental phase function data for a particle from Run 138 for λ = 457.9 nm compared with Mie theory for α = 14.1 and m = 1.723 - i0.007	94
A32	Experimental phase function data for a particle from Run 138 for λ = 488.0 nm compared with Mie theory for α = 14.6 and m = 1.674 - i0.010	95
A33	Experimental phase function data for a particle from Run 138 for λ = 514.5 nm compared with Mie theory for α = 15.6 and m = 1.613 - i0.0	96
A34	Experimental phase function data for a particle from Run 138 for λ = 457.9 nm	97
A35	Experimental phase function data for a particle from Run 138 for λ = 488.0 nm	98
A36	Experimental phase function data for a particle from Run 138 for λ = 514.5 nm	99
A37	Experimental phase function data for a particle from Run 138 for λ = 457.9 nm	100
A38	Experimental phase function data for a particle from Run 138 for λ = 488.0 nm	101
A39	Experimental phase function data for a particle from Run 138 for λ = 514.5 nm	102
A40	Experimental phase function data for a particle from Run 147 for λ = 457.9 nm	103
A41	Experimental phase function data for a particle from Run 147 for λ = 488.0 nm	104
A42	Experimental phase function data for a particle from Run 147 for λ = 514.5 nm	105

LIST OF TABLES

Table	-	Page
1	Identification of Samples Studied	25
2	Elemental Analysis of Various Samples	44
3	Results for dust particles for three wavelengths	58
4	Refractive indices of minerals	61

and the second of the second of the second measurement of the second of the second second second second second

SECTION 1

OBJECTIVES

The research objectives were to measure the light-scattering properties of dust particles generated thermally in solar furnace experiments performed by Science Applications Inc., and to determine the effects of particle size and shape and soil sample on the optical properties. The properties determined are:

- 1. Phase function (intensity vs scattering angle) for dust particles in the wavelength range 3500 \mathring{A} 7000 \mathring{A} .
- 2. Complex refractive index.
- Particle albedo (or absorption and extinction) for various wavelengths.

1.1 BACKGROUND

1.1.1 Light Scattering Theory

The optical properties of the blow-off particulates were determined from light scattering data using Mie theory to interpret the data. From Mie theory the intensity of the scattered light is established as a function of sphere radius, a, wavelength, λ , complex refractive index, $m=m_1-im_2$, and scattering angle, θ . The dimensionless size of the sphere, α , is defined by $\alpha=2\pi a/\lambda$. If α and m are known, the scattered intensity, I_s , as a function of angle θ for light polarized with the electric vector normal to the plane of scattering (the TM mode) are calculated from the equation,

$$I_{s} = \left| \sum_{n=1}^{\infty} \frac{2n+1}{n(n+1)} \left[a_{n} \pi_{n}(\cos \theta) + b_{n} \tau_{n}(\cos \theta) \right] \right|^{2}, \qquad (1)$$

where $\pi_n(\cos \theta) = P_n^{(1)}(\cos \theta)/\sin \theta$ (2)

$$\tau_{n}(\cos \theta) = \frac{d}{d\theta} P_{n}^{(1)}(\cos \theta)$$
 (3)

 $a_n = \frac{D_n(\beta) - m D_n(\alpha)}{D(\beta) - m G(\alpha)} \frac{j_n(\alpha)}{h(\alpha)}$ n = n(4)

$$a_n = \frac{m D_n(\beta) - D_n(\alpha)}{m D(\beta) - G(\alpha)} \frac{j_n(\alpha)}{h(\alpha)},$$

$$n \qquad n \qquad n \qquad n \qquad (5)$$

where

$$h_{n}(\alpha) = j_{n}(\alpha) + i N_{n}(\alpha)$$
 (6)

$$D_{n}(z) = (zj_{n})'/zj_{n}$$
 (7)

$$G_{n}(z) = (zh_{n})'/zh_{n}$$
 (8)

In the above equations h_n is the Hankel function, j_n is the spherical Bessel function, N_n is the Neumann function, $P_n^{(1)}$ is the Legendre function, and $\beta=m\alpha$.

Figures 1 and 2 show results of Mie theory calculations as three dimensional plots of the intensity ratio $\rm I_S/I_O$ (where $\rm I_O$ is the incident beam intensity)

as functions of the other parameters. Figure 1 demonstrates the effects of particle size and angle on I_S for a real refractive index m_1 = 1.696 (m_2 = 0 for Fig. 1), and Fig. 2 shows the effects of the imaginary component, m_2 , and angle for m_1 = 1.550 and α = 10. Figure 1 indicates that as α increases the number and intensity of the peaks in the angle range shown increase. Furthermore, the angular positions of the peaks and troughs depend on α (and m). This is what makes it possible to determine the size and refractive index from light-scattering data on I_S versus θ .




Figure 1. The dependence of scattered intensity I_s , on optical size α and angle θ for a refractive index m = 1.696 - i0.

Figure 2 illustrates an important consideration in the evaluation of \mathbf{m}_2 . As

 m_2 increases from zero (no energy absorption), the intensity profile becomes nearly independent of m_2 , and it becomes difficult to determine m_2 (and, hence, the albedo) for $m_2 > 0.05$ from light-scattering data.




Figure 2. The effects of scattering angle θ and m_2 on the scattering intensity for m_1 = 1.55 and α = 10.

The complicated topology shown in Figures 1 and 2 must be taken into

account in the analysis and interpretation of the data, for since α and m are initially unknown, the Mie theory equations must be used in an iterative scheme to determine them from the measured scattering function $I_s(\theta)$. The data analysis procedure is outlined below.

1.1.2 Principles of the Electrodynamic Balance

The scattering intensity profile, I_s (θ), has been measured by suspending a single, charged dust particle in an electrodynamic balance/light-scattering photometer developed by Davis and Ray 1 . A cross section of the electrodynamic balance is shown in Figure 3, and an exploded view of the device is shown in Figure 4. The endcap electrodes have geometries described by the equation

$$z^2 - \frac{r^2}{2} = z_0^2 \tag{9}$$

where $2z_0$ is the minimum distance between the endcap and the ring electrode geometry satisfies the equation

$$z^2 - \frac{r^2}{2} = -z_0^2 \tag{10}$$

The ring electrode was connected to an ac power supply (usually a 60 hz transformer) to focus the charged particulate on the centerline (vertical axis) of the balance. With no dc field applied the particle oscillates about a point below the midplane of the balance. When a dc field is applied to offset the gravitational force on the particle it remains stationary at the midplane (z=0) between the endcaps.

Davis, E.J. and Ray, A.K., "Single Aerosol Particle Size and Mass Measurements Using an Electrodynamic Balance," J. Colloid and Interface Sci., 75(2), 566-576, 1980.




Figure 3. The electrodynamic balance/light scattering photometer and peripheral equipment.




Figure 4. An exploded view of the electrodynamic balance

If, for a negatively charged particle, a dc voltage, $+V_{\rm dc}$ is applied to the upper electrode and $-V_{\rm dc}$ is applied to the lower endcap, the electric field near the null point (midplane) of the balance is given by

$$E_{dc,z} = C \frac{V_{dc}}{z_0}, \qquad (11)$$

where C is a geometrical constant which takes into account the shape of the electrodes and the edge effects.

For a particle of mass, m_p , and charge, q, the particle is balanced when the following force balance is satisfied

$$qE_{dc,z} - m_p g = 0, \qquad (12)$$

where g is the gravitational acceleration constant. The dc voltage required to balance the particle is given by

$$V_{dc} = \frac{m_p g z_0}{g C} \tag{13}$$

As indicated in Figure 4, a laser beam was aligned to pass through the center of the chamber, and a window and slit in the ring electrode permitted detection of the scattered light by means of a transversing photomultiplier tube. The photodetector was driven by a stepping motor, and the signals from the photodetector (intensity) and the stepping motor (angle) were digitized and recorded using a Digital Equipment Corporation MINC-23 computer. Additional details of the experimental system are provided in the next section.

SECTION 2

THE EXPERIMENTAL APPARATUS AND DATA ANALYSIS

2.1 THE EXPERIMENTAL SYSTEM

contract the second of the sec

The components of the experimental system are indicated in Figure 5. The dc power supplies were matched and connected to a dual potentiometer to permit precise balancing of the charged particulate, observed through a low-power microscope attached to the balance frame. Dust particles were washed from the filters or wall-wiping material to form a dilute suspension in water, and the suspension was drawn into a microliter syringe. The needle of the syringe was connected to a high voltage dc supply to facilitate charging.




Figure 5. The electrical circuitry for the picobalance.

Injection of a dust particle into the balance was accomplished by forming a

small droplet at the top of the needle, switching on the high voltage, and adjusting the ac voltage to "catch" the droplet. The water surrounding the particulate quickly evaporated, leaving the charge on the particle. The dc voltage was then applied to the endcaps to stabilize the particle at the center of the balance. Usually a dust particle was suspended for more than one hour prior to obtaining a light-scattering data to insure that the water was removed.


After no mass change could be detected, the laser intensity and voltage input to the photomultiplier tube were adjusted to give a favorable signal-to-noise ratio, indicated by recording the scattered intensity as a function of angle on an X-Y recorder. Next the computerized data acquisition was carried out.

The laser light sources provided vertically polarized (TM mode) light at any of several discrete wavelengths. Two sources were available: (i) a 10 mW Spectra Physics helium-neon laser (632.8 nm) and (ii) a Coherent Innova 90-5 5W argon-ion laser. A tunable dye laser was available, but was not used for the results reported here because the argon-ion laser had a sufficient range of wavelengths in the visible. The wavelengths used were 457.9, 488.0 and 514.5 nm.

For data acquisition the signals from the photomultiplier tube and the stepping motor were conditioned to be in the voltage range 0-5 V by means of operational amplifiers, and these signals were digitized and recorded using a DEC MINC-23 computer system. The computer data acquisition was activated by triggering the computer clock with a signal from the stepping motor, and the sampling rate was selected to obtain about 500 data points during a forward scan (from about 6° to 174°) and the same number during a reverse scan. Data-taking stopped after the completion of one forward-reverse scan cycle.

Figure 6 shows typical raw data for a forward scan, plotted on the HP 7245 B Printer/Plotter as intensity (PMT output voltage) versus angle

(Stepping motor voltage). Two sharp troughs should be noted at about 1.35 volts and 3.78 volts. These minima in the scattered intensity were caused by the blockage of the light by two pegs installed to provide calibration of the voltage signal from the stepping motor. The raw data (PMT output voltage versus stepping motor voltage) were examined, using appropriate computer software, to determine the voltages at which the sharp troughs occurred. These stepping motor voltages, then, corresponded to the angles 16.2° and 163.8°.



Contraction of the second

Contract | Contract - Contract | Contract | Contract |

Figure 6. Raw light scattering data from a dust particle, λ = 457.9 nm

After a scan cycle was completed the wavelength of the laser was changed, and the experiment repeated. At the end of a sequence of experiments on a particular dust particle the particle was expelled from the balance, and the

background signal was measured and recorded at each wavelength. Figure 6 shows both the data obtained with a dust particle suspended in the beam and the background. The data used in further analysis was the difference between the two signals.

2.2 INTERPRETATION OF THE DATA

To determine the particle size and refractive index from data of the type shown in Figure 5 Mie theory was applied. Forty data points uniformly spaced on the angle axis were selected, usually in the range 30° - 130° , and the intensities, I predicted from Mie theory for these angles were calculated. The voltages from the photodetector circuit were converted to normalized intensities using the relation

$$I_{e}(\theta_{i}) = \sigma[V(\theta_{i}) - V_{b}(\theta_{i})], \qquad (14)$$

where σ is a scale factor, $V(\theta_i)$ is the signal at the i^{th} angular position, $V_b(\theta_i)$ is the background signal (no particle present) at that position and $I_e(\theta_i)$ is the experimental intensity at θ_i . The scale factor, σ , can be determined in a number of different ways. One method is to use the maximum (highest peak in the light scattering profile) and minimum (lowest trough in the profile) detector signals to normalize $I_e(\theta_i)$, that is, define σ by

$$\sigma = \frac{1}{(V_{\text{max}} - V_{\text{min}})} \tag{15}$$

This method places too much emphasis on only two points of the light scattering profile, for if there is excessive noise in the signal, significant

error is introduced in the normalization. A better approach is to consider σ a parameter in the optimization procedure used to compare the experimental intensities with those computed from Mie theory.

To interpret the experimental data we determined values of α , m (m = m₁ - im₂) and σ that minimize the function

$$F(\alpha,m,\sigma) = \sum_{i=1}^{N} w_i \mid f_i \mid^2, \qquad (16)$$

where f_i is the ith residual defined by

$$f_{i} = I_{e}(\theta_{i}) - I_{t}(\theta_{i}), \qquad (17)$$

and w_i is the weighting factor. For these studies N was usually 40, and the most suitable weighting factor was found to be $w_i = \sin^2\theta_i$.

To minimize the objective function, $F(\alpha,m,\sigma)$ we applied the Levenberg-Marquardt algorithm (Marquardt²), which performs an optimum interpolation between the Taylor series and gradient (steepest descent) methods. The Gauss-Newton method of optimization depends upon reduction of the residual, f_i , to linear form by first order Taylor approximations taken about an initial or trial solution for the parameters. This method frequently fails because of divergence of successive iterations, so various modifications of the method of steepest descent have been introduced to avoid such divergence, but the method of steepest descent can give agonizingly slow convergence after the first few

Marquardt, D.W., "An Algorithm for Least-Squares Estimation of Nonlinear Parameters," J. of the Society of Industrial Applied Mathematics, 11(2), 431-441, 1963.

iterations. The Levenberg-Marquardt algorithm avoids the worst features of the older methods.

After the optimal values of the parameters were obtained, the theoretical intensities computed were graphed together with the experimental data, and the results are displayed in the next section.

SECTION 3

RESULTS

3.1 SAMPLE INDENTIFICATION

To identify the dust samples in this report we shall use the run numbers used by Science Applications, Inc. [Trip Reports, March 1980 and September 1980, DNA Soil Test Program at the CNRS 1000 KW Solar Furnace, Odeillo, France, November 24, 1980]. Table 1 lists the run numbers, soil type codes and description for each of the samples studied herein.

The samples described above as wall wipings were particulates washed from towelling used to remove dust from the furnace walls. Very little dust was found in filter samples, and it was difficult to wash dust out of the filter matrix.

3.2 ELECTRON MICROSCOPY

A scanning electron microscope equipped for elemental analysis by energy dispersion x-ray spectrometry (EDAX) was used to examine the sizes, shapes and elemental analyses of dust particles in the samples. Figures 7 and 8 are scanning electron micrographs (SEM) of loose thermal dust collected from the solar furnace and wall wipings, respectively, for Run 57, and they illustrate the range of sizes (note the 100 µm bars at the bottom of each picture) and the shapes encountered. Approximately half of the particulates shown in these figures are spherical or near-spherical, indicating that the temperatures reached were sufficient to melt many of the chemical species present.

Table 1. Identification of samples studied

SAI Run No.	Soil Type Code	Description
57	Silt P-14	Wall wipings and
		Bottom filter
60	Clay P-13	Wall wipings
69	RB5I-2	Wall wipings and
		Bottom filter
101		Wall wipings
104	RC5Y-2	Wall wipings
107	RC4U-2	Wall wipings
108	RD5I-2	Wall wipings
136	Soil RBU2#15	Wall wipings
138	Gray tile	Wall wipings
147	Local vegetation	Wall wipings and
		Bottom filter
1180	5F	Wall wipings




Figure 7. An SEM of loose dust from Run 57



Figure 8. An SEM of wall wipings from Run 57.

Figures 9 and 10, on the otherhand, show many particles of irregular shape and relatively large size (dimensions > 100 μ m) for loose material from Runs 69 and 1180, respectively. Such large particles would be expected to have fairly rapid settling rates and were not found in the filters. It is clear from Figure 7-10 that the range of particle sizes is very great, and Figure 11-13 for Run 136 show that wide ranges of sizes and shapes are encountered in a single run. The three figures were obtained by increasing the magnification from X200 to X2400. At a magnification of X200 many agglomerated particulates can be seen (Figure 11), and at the higher magnifications a very large number of irregularly shaped particles are seen.

A set of SEM and the corresponding EDAX analyses are shown in Figure 14 through 26 for the runs listed in Table 1. Several of the EDAX analyses show large peaks corresponding to gold (Au) and palladium (Pd), for these elements were used to shade the particulates for some of the SEM. The SEM selected are for various magnifications; some show relatively large regions of a sample, and others focus on specific particulates. Table 2 summarizes the main elements detected in the samples.




Figure 9. An SEM of loose dust from Run 69.





Figure 10. An SEM of loose dust from Run 1180.



THE RESIDENCE OF THE PARTY OF T

A Processe accessed progress processed

Figure 11. An SEM of wall wipings from Run 136 at lower magnification (X200).




Figure 12. An SEH of wall wipings from Run 136 for a magnification




Figure 13. An SEM of wall wipings from Run 136 at high magnification (X2400).




Figure 14 a,b. An SEM and elemental analysis (EDAX) for a bottom filter from Run 57.




Figure 15 a,b. An SEM elemental analysis for a wall wiping from Run 57.




Figure 16 a,b. An SEM and elemental analysis for a wall wiping from Run 60.




Figure 17 a,b. An SEM and elemental analysis for a wall wiping from Run 69.






Figure 18. An SEM elemental analysis for a bottom filter from Run 69.






Figure 19 a,b. An SEM and elemental analysis for a wall wiping from Run 101.







Figure 20 a,b. An SEM and elemental analysis for a wall wiping from Run 104.





AND THE PERSON OF THE PERSON O

Figure 21 a,b. An SEM and elemental analysis for a wall wiping from Run 107.






Figure 22 a,b. An SEM and elemental analysis for a wall wiping from Run 108.






Figure 23 a,b. An SEM and elemental analysis for a wall wiping from Run 136.






Figure 24 a,b. An SEM and elemental analysis for a wall wiping from Run 138.





AND RECORD AND RESPONDED TO SECURITY OF THE PROPERTY OF THE PR

Figure 25 a,b. An SEM and elemental analysis for a wall wiping from Run 147.






Figure 26 a,b. An SEM and elemental analysis for a wall wiping from Run 1180.

Table 2. Elemental analysis of various samples

Run No.	Main Elements	Trace Elements
57	Al,Ca,K,Na,Si	Fe
60	Al,Ca,Fe,K,Si	Ag
69	Al,Ca,K,Na,Si	Ag,Fe,Cu
101	Al,Si	
104	Al,Si	Cu
107	Al,Ca,Si	Cu,Fe
108	Si	Cu
136	Al,Ca,Fe,K	Cu
138	Ag,Al,Ca,Si	Fe
147	Al,Cl,K,Mg,Si	Cu
1180	Al,Ca,Si	Cu

Most of the samples consisted of mixed silicates of aluminum, calcium and potassium, and samples from Runs 57 and 69 contained sodium compounds. Iron was found in significant amounts in samples from Runs 60 and 136, and iron and copper were present in trace amounts in most samples. The iron and copper might have been in the form of oxides, but quantitative analysis and information on the chemical species encountered were not possible with the techniques used.

Samples from Run 147 were found to be different from the others in that magnesium and chlorine were detected in these samples which came from local vegetation. Run 136 has some unique features, for Figure 11-13 show agglomerated particles and particles that might be of biological origin (e.g., spaces).

Because spherical particulates are not seen (see Figure 13 and 23a) it appears that the temperatures encountered in Run 136 were too low to melt silicates.

3.3 LIGHT SCATTERING PHASE FUNCTIONS


several interfered britished conserva-

Figure 27-32 are representative plots of scattered intensity versus angle for various samples at various wavelengths, and a complete set of raw data are given in Appendix A. The figures shown in this section correspond to data for which the optimization program converged to yield values of size $\alpha = \pi D_p/\lambda$ and refractive index $m = m_1 - im_2$. For many experiments no satisfactory match between the measured phase functions and Mie theory was achieved, so for experiments only raw data are given in the appendix.

For many runs only the angle range from about 20° to 100° was examined, but with the redesign of the viewing window more recent data cover the range from about 20° to 160°. The pegs used to calibrate the stepping motor voltage prevented the collection of data beyond this range.


Figures 27-29 show a set of data for a thermal dust particle from Run 60 obtained at three different wavelengths. The agreement between experimental and calculated phase functions is fairly good here, considering that the data are "noisy", but there is a rather larger scatter in the values of particle diameter, D_p , calculated from the values of α obtained from the data analysis. The calculated particle diameters are 0.730 μm , 0.763 μm and 0.881 μm with a mean of 0.791 μm . The scatter about the mean is about $\pm 10\%$. There is also scatter in the values of m_1 , and m_2 from the data, but the refractive index can be expected to vary with wavelength, and more will be said on that point below.

A second set of three runs, which cover a different range of angles, is presented as Figures 30-32 for Run 1180. Note that there is backscatter shown in




Experimental phase function data (*) for a particle from Run 60 for λ = 457.9 nm compared with Mie theory (—) for α = 5.01 and m = 1.705 - i0.054. 27. Figure

See Legisle Protectal Research Protection Legisles



CONTROL STATES STATES (STATES STATES STATES

Experimental phase function data (*) for a particle from Run 60 for λ = 488.0 nm compared with Mie theory (--) for α = 4.91 and m = 1.590 - i0.049. 28. Figure



Control of the Contro

BESTERNAL RESERVED TO THE SECOND


Experimental phase function data (*) for a particle from Run 60 for λ = 514.5 nm compared with Mie theory (--) for α = 5.38 and m = 1.571 - i 0.018. 29. Figure

these figures. The particle diameters calculated for this particle from the three experiments are 1.401 µm, 1.429 µm and 1.523 µm with a mean of 1.451 µm. the scatter is only about $\pm 5\%$ for this set. There is rather little variation in refractive index for these three runs, as shown in Table 3, which summarizes the results for the runs for which convergence of the matching procedure occurred. Also given in the table are the calculated albedos for each run and the average values of α , m_1 , m_2 for each particle measured at more than one wavelength. Average values of the parameters permit us to compute more comprehensive phase function plots, and Figures 33-35 show composite phase functions for particles from several runs. These figures are based on the mean values of α , m_1 and m_2 reported in Table 3 for each set of data on a particular dust particle.

Control territorial controls controls and the controls of the control of the cont


Actional services (services lessons)


Additional comparisons between measured phase functions and Mie theory results are given in the appendix, and many of the comparisons show poor agreement with the detailed structure of the intensity profile but broad agreement with the positions of peaks, troughs and general structure. This might be expected of particulates that are not perfect spheres but have blemishes due to outgassing or other phenomena that occurred during solidification after the particle melted.





per l'écococie persenti celebras assesses printes appearent necesses

50










Computed phase functions based on mean values of α and m for particles from Runs 69 (*), 104 (#) and 107 (+). Figure 34.



SECTION 4


DISCUSSION OF RESULTS

Table 3 shows that the values of m_2 determined by comparing phase function data with Mie theory are relatively small (compared with strongly absorbing particulates such as carbon or soot particles for which $m_2 > 0.6$) and scattered. Since m_2 strongly affects the computed albedo, the latter is also scattered. For the small values of m_2 encountered here it is difficult to determine m_2 from noisy phase function data for the reasons suggested by Figure 36, which shows calculated phase functions for a sphere with $\alpha = 10$, $m_1 = 1.600$ and various values of m_2 . The primary effect of increasing m_2 is to decrease the intensity of the scattered light without appreciably shifting the angular positions of peaks and troughs. Thus, it is difficult to extract accurate values of m_2 by inverting the phase function information. The values of m_2 reported here should be construed to be only order of magnitude estimates.

entertation and interest in president

The range of dust particle sizes studied with the electrodynamic balance is considerably smaller than the range of particles shown in the scanning electron micrographs. There are two likely reasons for this discrepancy (i) the number density of micron-size particulates is very much greater than that of larger particulates (say, $D_{\rm p} > 20~\mu \rm m$), and (ii) larger particulates injected into the electrodynamic balance have much larger settling velocities than small ones, so the latter are preferentially captured. Efforts were made to randomize the sampling, but few large particulates were encountered in the light-scattering studies.

More than one-half of the particulates studied in the electrodynamic balance could not be compared with Mie theory, for they were not spherical. One indication of asymmetry of a particulate was that when observed through the



= 1.6 and Computed phase functions for a sphere for $\alpha=1.6$ m $_{\rm l}$ = 0.0 (*), 0.025 (#) and 0.05 (+).

Table 3. Results for dust particles for three wavelengths Albedo RUN λ,nm a,µm Run 57 P-14 Wall wipings 457.9 12.60 1.551 0.003 0.8385 0.9183 $V_{ac} = 768.0$ 0.9921 488.0 12.77 1.525 0.004 0.8199 $V_{dc} = 0.0$ 514.5 12.89 1.508 0.005 0.8022 1.056 AVERAGE 12.75 1.528 0.004 0.8202 0.9888 Run 60 P-13 Wall wipings 457.9 5.008 1.705 0.054 0.4917 0.365 $V_{ac} = 1176.0$ 488.0 4.. 910 1.590 0.049 0.6216 0.3814 $V_{dc} = 112.0$ 514.5 5.378 1.571 0.018 0.7578 0.4404 **AVERAGE** 5.099 1.622 0.6237 0.3956 0.040 Run 60 P-13 Wall wipings 457.9 4.604 1.626 0.036 0.6688 0.3355 $V_{ac} = 768.0$ 4.841 1.600 0.030 0.7054 488.0 0.376 $V_{dc} = 33.1$ 514.5 4.618 1.633 0.026 0.7213 0.3782 **AVERAGE** 0.031 0.6985 0.3632 4.688 1.620 Run 69 RB5I-2 Wall wipings 457.9 12.53 1.562 0.003 0.8501 0.9130 $V_{ac} = 600.0$ 488.0 0.8164 0.9194 11.84 1.557 0.005 $V_{dc} = 0.466$ 514.5 11.44 1.490 0.012 0.7502 0.9370

11.94

1.536

0.006

0.8056

0.9231

AVERAGE

RUN	λ,nm	<u>a</u>	<u>m</u> 1	^m 2	Albedo	a,µm
Run 104 RC5Y-2 Wall wipings	457.9	12.23	1.601	0.024	0.5589	0.8915
V _{ac} = 888.0	488.0	12.18	1.593	0.007	0.7619	0.9463
V _{dc} = 0.906	514.5	12.38	1.573	0.008	0.7243	1.014
AVERAGE		12.26	1.589	0.013	0.6817	0.9506
Run 107 P-14 Wall wiper						
sample RC4U-3	457.9	13.65*	1.594*	0.006*	0.8028*	0.9948
V _{ac} = 768.0	488.0	12.40	1.574	0.007	0.7417	0.9631
$V_{dc} = 0.792$	514.5	12.53	1.559	0.005	0.7816	1.026
AVERAGE		12.86	1.576	0.006	0.7754	0.9946
Run 108 Wall wipings	457.9	12.75	1.529	0.005	0.8013	0.9291
V _{ac} = 744.0	488.0	12.88	1.510	0.005	0.796	1.000
$V_{dc} = 0.675$	514.5	13.08	1.481	0.007	0.78	1.0711
AVERAGE		12.90	1.507	0.006	0.7924	1.000
Run 136 RBU2 #15 Wall						
wipings	457.9	-	-	•	-	-
$V_{ac} = 1032.0$	488.0	12.40	1.582	0.002	0.8861	0.9632
/ _{dc} = 0.695	514.5	-	-	-	-	-

AVERAGE

12.40 1.582 0.002

0.8861

0.9632

^{*} extrapolated

Table 3. Results for dust particles for three wavelengths (Concluded)						
RUN	λ,nm	α.	m ₁	m ₂	Albedo	a,μm
Run 138 Black Tile Wall						
wipings	457.9	14.14	1.723	0.007	0.7091	1.0303
V _{ac} = 768.0	488.0	14.59	1.674	0.010	0.6716	1.1332
V _{dc} = 1.27	514.5	15.06	1.613	0.000	0.9892	1.2333
AVERAGE		14.60	1.670	0.006	0.79	1.1323
Run 1180 Wall 5-F	457.9	9.61	1.719	0.029	0.5531	0.7004
V _{ac} = 1824.0	488.0	9.20	1.716	0.001	0.9369	0.7145
V _{dc} = 62.0	514.5	9.30	1.709	0.026	0.5768	0.7615
AVERAGE		9.37	1.715	0.019	0.689	0.7255

microscope eyepiece on the picobalance the particle "twinkled" due to irregular scattering as it rotated. Light-scattering data taken with such particles showed no reproducibility during forward and backward scans of the traversing photomultiplier tube, and those data are not included in this report.

The real parts of the refractive indices determined in this research are generally consistent with refractive indices reported for minerals (silicates, clay, mica, etc.). Table 4 lists typical values of m₁ for feldspars, clay, mica and other silicates containing Al, Ca, Mg and Na. The range of values listed in Table 4 is about the same as that determined here for the various soil samples.

There is no clearcut dependence of refractive index on wavelength for the wavelengths studied here and in Phase I of the project (457.9 nm - 632.8 nm), but is is to be expected that in the ultraviolet region of the spectrum m_2 is larger, for the silicates can be expected to absorb in the UV range.

There is also no well-defined variation in optical properties from one soil sample to another, for variations between individual particles in a single sample are large. That is clear from an examination of the SEM data in Section 3, for the particulates vary greatly in size, structure and melting points.

Table 4. Refractive indices of minerals

NAME	FORMULA	REFRACTIVE INDEX, m ₁
Andesine	(CaO,Na ₂ O)Ai ₂ O ₃ •4SiO ₂)	1.549
Anorthite	CaO•Ai ₂ O ₃ •2SiO ₂	1.5755
Anorthoclase	(Na,K) ₂ 0•Ai ₂ 0 ₃ •6Si0 ₂	1.523
Laboradorite	NaAiSi308 + CaAi2Si208	1.559
Oligoclase	NaAiSi ₃ 0 ₈ + CaAi ₂ Si0 ₈	1.539
Orthoclase	K ₂ 0•Ai ₂ 0 ₃ •6Si0 ₂	1.518
Wollastonite	CaSiO ₃	1.616
Kaolinite (china clay)	Ai ₂ 0 ₃ ·2Si0 ₂ ·2H ₂ 0	1.561
Muscovite (white mica)	K ₂ 0•3Ai ₂ 0 ₃ •6Si0 ₂ •2H ₂ 0	1.561
Analcite	NaA1Si ₂ 0 ₆ •H ₂ 0	1.479-1.493
Andalusite	Ai ₂ 0Si0 ₄	1.629-1.640
Clinozoisite	Ca ₂ A1 ₃ Si ₃ O ₁₂ (OH)	1.670-1.715
Enstatite	MgSiO ₃	1.650-1.662
Forsterite	Mg ₂ SiO ₄	1.635
Gehlenite	Ca ₂ Al ₂ SiO ₇	1.669
Kyanite	A1 ₂ 0Si0 ₄	1.712-1.718


APPENDIX I

EXPERIMENTAL PHASE FUNCTION DIAGRAMS FOR THE DUST PARTICLES

The following phase function diagrams are presented in the same order of increasing run number used for Figures 14-26. In some cases the experimental data are compared with Mie theory, but in others the inversion of the phase function data by means of the iterative optimization procedure discussed in Section 2 did not converge, so the parameters α , m_1 and m_2 could not be determined.


CONTROL CARREST SURFACE CARREST BEFORE SUBSECT SUBSECT PROSPECTOR PROSPECTOR








AND THE PROPERTY OF THE PROPERTY SERVICE PROPERTY SERVICE SERVICE SERVICE SERVICE SERVICE SERVICES


Experimental phase function data (*) for a particle from Run 57 for $\lambda=457.9$ nm compared with Mie theory (--) for $\alpha=12.6$ and m = 1.55 - i0.003. A1. Figure













Experimental phase function data (*) for a particle from Run 57 for $\lambda = 514.5$ nm. Figure A6.




Experimental phase function data (*) for a particle from Run 60 for $\lambda=457.9$ nm compared with mie theory (—) for $\alpha=4.60$ and m = 1.626 - i0.036. Figure A7.




Terrorea leavence representation appropriate proposed services services between the services and the services are services are services and the services are services are services and the services are services are services.

Experimental phase function data (*) for a particle from Run 60 for $\lambda=488.0$ nm compared with Mie theory (--) for $\alpha=4.84$ and m = 1.600 - i0.030. Figure A8.




Experimental phase function data (*) for a particle from Run 60 for $\lambda=514.5$ nm compared with Mie theory (—) for $\alpha=4.62$ and m = 1.633 - i0.026. A9. Figure


sycal assessed beeseese tasesses, copeants sessesses




test testestest testestest betestest attestest sectestes sectestes sectestes sectestes sectestes

73







Experimental phase function data (*) for a particle from Run 69 for $\lambda=514.5$ nm compared with Mie theory (—) for $\alpha=11.4$ and m = 1.490 - i.0.012. Figure Al2.




SERVICE CONTRACT CONT


Experimental phase function data (*) for a particle from Run 69 for $\lambda = 457.9$ nm. Figure Al3.






THE PARTIES SERVICE LIBERTY OF THE PARTIES OF THE P








RESERVED THE PROPERTY OF THE P


Experimental phase function data (*) for a particle from Run 104 for $\lambda=514.5$ nm compared with Mie theory (—) for $\alpha=12.4$ and m = 1.573 - i0.008. Figure Al8.




STATES - 457775 400 STATES

BOOK SAN TO SERVICE STATE OF THE SERVICE STATE STATE OF THE SERVICE STAT


Experimental phase function data (*) for a particle from Run 107 for $\lambda=488.0$ nm compared with Mie theory (—) for $\alpha=12.4$ and m = 1.574 - i0.007. A19. Figure




Experimental phase function data (*) for a particle from Run 107 for λ = 514.5 nm compared with Mie theory (—) for α = 12.5 and m = 1.559 - i0.005. A20.




Experimental phase function data (*) for a particle from Run 108 for $\lambda=457.9$ nm compares with Mie theory (—) for $\alpha=12.8$ and m = 1.529 - i0.005. A21. Figure



Experimental phase function data (*) for a particle from Run 108 for $\lambda=488.0$ nm compared with Mie theory (--) for $\alpha=12.9$ and m = 1.510 - i0.005. Figure A22.




Experimental phase function data (*) for a particle from Run 108 for λ = 514.5 nm compared with Mie theory (—) for α = 13.1 and m = 1.481 - i0.007. Figure A23.




SECTION OF SECTION SEC

Experimental phase function data (*) for a particle from Run 136 for $\lambda=488.0$ nm compared with Mie theory (—) for $\alpha=12.4$ and m = 1.582 - i0.002. Figure A24.





the property of the property o

Experimental phase function data (*) for a particle from Run 136 for λ = 457.9 nm. Figure A25.




Experimental phase function data (*) for a particle from Run 136 for λ = 488.0 nm. Figure A26.







essel incorrect institute legerates exercise recover recovery consists consists between




Experimental phase function data (*) for a particle from Run 136 for λ = 488.0 nm. A29. Figure






Experimental phase function data (*) for a particle from Run 138 for $\lambda=457.9$ nm compared with Mie theory (—) for $\alpha=14.1$ and m = 1.723 - i 0.007. A31. Figure






MICROCOPY REJOLUTION TEST CHART
NATIONAL BUREAU OF STANDARDS - 1963 - A



CONTRACTOR CONTRACTOR CONTRACTOR


second between branch

95




CONTROL CONTROL SECRETARY CONTROLS CONTROLS CONTROLS CONTROLS CONTROLS

96





Indicated the state of the stat

97




Experimental phase function data (*) for a particle from Run 138 for λ = 488.0 nm. A35. Figure







Experimental phase function data (*) for a particle from Run 138 for λ = 457.9 nm. Figure A37.





Experimental phase function data (*) for a particle from Run 138 for $^{\lambda}$ = 488.0 nm. Figure A38.



Experimental phase function data (*) for a particle from Run 138 for λ = 514.5 nm. Figure A39.







Experimental phase function data (*) for a particle from Run 147 for λ = 514.5 nm. A42.

DEPARTMENT OF DEFENSE

Defense Intelligence Agency ATTN: RTS-2A, Tech Library ATTN: RTS-2B

Defense Nuclear Agency ATTN: SPAS, G. Ullrich 4 cys ATTN: STTI-CA

Defense Technical Information Canter 12 cys ATTN: DD

Field Command, Defense Nuclear Agency ATTN: FCPR ATTN: FCTT ATTN: FCTT, W. Summa ATTN: FCTXE

Joint Strat Tgt Planning Staff ATTN: JLKS ATTN: JPTM

Under Secy of Def for Rsch & Engrg
ATTN: Strat & Space Sys (OS)
ATTN: Strat & Theater Nuc For, F. Vajda

DEPARTMENT OF THE ARMY

BMD Advanced Technology Center

ATTN: ATC-T

BMD Systems Command ATTN: BMDSC-LEE, R. Webb

Harry Diamond Laboratories

ATTM: DELHD-NW-P ATTM: DELHD-TA-L, 81100, Tech Library

US Army Ballistic Research Lab ATTN: DRDAR-BLA-S, Tech Library ATTN: DRDAR-BLT, J. Keefer

US Army Corps of Engineers ATTN: DAEN-ECE-T

US Army Engineer Ctr & Ft Belvoir ATTN: Tech Library

US Army Engineer Div, Huntsville ATTN: HNDEN-FO

US Army Nuclear & Chemical Agency

ATTN: Library ATTN: MONA-WE, J. Uecke

DEPARTMENT OF THE NAVY

Naval Research Laboratory
ATTN: Code 4040, D. Book
ATTN: Code 4040, J. Boris
ATTN: Code 2627, Tech Library

Naval Surface Weapons Center ATTN: Code F31 ATTN: Code R44, H. Glaz ATTN: Code X211, Tech Library

DEPARTMENT OF THE NAVY (Continued)

Naval Surface Weapons Center ATTN: Tech Library & Info Svcs Br

DEPARTMENT OF THE AIR FORCE

Air Force Institute of Technology ATTN: Library

Air Force Weapons Laboratory

ATTN: NTED-A ATTN: SUL

Assist Ch of Staff, Studies & Analysis ATTN: AF/SAMI, Tech Info Div

Ballistic Missile Office/DAA ATTN: ENBF, D. Gage ATTN: ENSN ATTN: MGEN, A. Schenker ATTN: PP

Strategic Air Command ATTN: NRI/STINFO

DEPARTMENT OF ENERGY

Los Alamos National Laboratory ATTN: C. Keller ATTN: M. Sandford ATTN: R. Whitaker

Sandia National Laboratories

ATTN: Div 1111, J. Reed ATTN: J. Bannister ATTN: Org 7112, A. Chabai

OTHER GOVERNMENT AGENCY

Central Intelligence Agency ATTN: OSWR/NED

DEPARTMENT OF DEFENSE CONTRACTORS

Acurex Corp ATTN: C. Wolf

Aerospace Corp ATTN: H. Mirels ATTN: Library Acquisition M1/199

Applied Research Associates, Inc ATTN: N. Higgins

Applied Research Associates, Inc ATTN: D. Peipenburg

Applied Theory, Inc ATTN: J. Trulio

107

Boeing Co ATTN: Aerospace Library ATTN: S. Strack

California Research & Technology, Inc

ATTN: K. Kreyenhagen ATTN: Library

DEPARTMENT OF DEFENSE CONTRACTORS (Continued)

California Research & Technology, Inc ATTN: F. Sauer

Carpenter Research Corp ATTN: H. Carpenter

University of Denver ATTN: Sec Officer for J. Wisotski

HåH Consultants, Inc ÅTTN: J. Haltiwanger ATTN: W. Hall

H-Tech Labs, Inc ATTN: B. Hartenbaum

Kaman Sciences Corp ATTN: R. Ruetenik

Kaman Tempo ATTN: DASIAC

Kaman Tempo ATTN: DASIAC

McDonnell Douglas Corp ATTN: H. Herdman ATTN: R. Halprin

Mission Research Corp ATTN: C. Longmire

University of New Mexico ATTN: G. Leigh 2 cys ATTN: D. Calhoun

University of New Mexico ATTN: J. Kovarna

Nichols Research Corp. Inc ATTN: N. Byrn

Pacific-Sierra Research Corp ATTN: H. Brode, Chairman SAGE

Pacific-Sierra Research Corp ATTN: D. Gormley

Pacfica Technology ATTN: R. Allen ATTN: Tech Library

Patel Enterprises, Inc ATTN: M. Patel

Physical Research, Inc ATTN: R. Deliberis ATTN: W. Mendes

Physics International Co ATTN: H. Wampler

Control of Programme

DEPARTMENT OF DEFENSE CONTRACTORS (Continued)

R&D Associates ATTN: A. Kuhl ATTN: P. Haas ATTN: Tech Info Center

Rand Corp ATTN: B. Bennett

S-CUBED ATTN: C. Dismukes ATTN: J. Barthel ATTN: K. Pyatt ATTN: Library

S-CUBED ATTN: C. Needham

Science & Engrg Assoc, Inc ATTN: B. Chambers

Science Applications International Corp ATTN: G. Binninger

Science Applications Intl Corp ATTN: H. Wilson ATTN: R. Schlaug ATTN: Tech Library

Science Applications Intl Corp ATTN: J. Cockayne ATTN: W. Layson

SRI International ATTN: G. Abrahamson ATTN: J. Colton ATTN: Library

Teledyne Brown Engineering ATTN: B. Hartway ATTN: D. Ormond ATTN: F. Leopard

TRN Electronics & Defense Sector ATTN: N. Lipner ATTN: Tech Info Center

TRN Electronics & Defense Sector
ATTN: E. Wong
ATTN: G. Hulcher
ATTN: P. Dai

University of Washington 2 cys ATTN: E. Davis 2 cys ATTN: R. Periasamy

Weidlinger Assoc, Consulting Engrg ATTN: I. Sandler

5-86